

## A baseline for evaluating ergonomic interventions for Construction Glass and Glazing Work

### **Ergonomic Back Injury Risk Factors in Construction Glass and Glazing Work**

*Terry L. Stentz, Changbum R. Ahn, Kelli R. Herstein, and Zahra Jabbarani Torghabeh. CPWR Report, 2019.*

#### **Overview**

Construction glass and glazing (CGG) workers have high rates of work-related musculoskeletal disorders (WRMSDs). For this study, the researchers conducted interviews with CGG workers and worksite observations to identify problems leading to the higher rates of WRMSDs and to gather information about improvements that are needed to lower the risk for injury. CGG job tasks were classified in five categories, and ergonomic task-based estimates were done using the Posture, Activity, Tools, and Handling (PATH) method. The CGG workers' level of risk of developing musculoskeletal injuries was scaled using the Rapid Entire Body Assessment (REBA) method. The results of this study provided a baseline database for future evaluations of ergonomic interventions to reduce CGG workers' risk for injury.

#### **Key Findings**

- The hardest most challenging CGG job tasks are manual material handling (MMH) of heavy materials for a long period time, handling material in a dirty or muddy environment, working above head, and working in intense weather.
- The PATH assessment identified the major CGG ergonomic tasks as glass/panel installation, frame installation, finishing jobs, and loading/unloading. MMH was a major activity for frame installation and glass/panel and loading/unloading tasks, and among finishing job activities, applying or pushing caulking bead ranked at the top.
- CGG workers spent 92% of their time standing or walking, and 27% of their time in non-natural trunk postures. Glaziers spent 21% of the time with one or two elbows at or above shoulder height.
- Frame installation, glass/panel installation, and loading/unloading activities had medium and high WRMSD risk levels based on REBA scores. MMH activity had the highest REBA score and WRMSD risk level for all frame, glass/panel and loading/unloading task activities.
- Cuts, lacerations, and bruises, as well as back and shoulder injuries were the most frequently reported injuries reported by participants.
- Suggestions for safety and productivity improvements to reduce the risks associated with MMH included using more powered and unpowered mechanical handling equipment (if appropriate), additional worker assistance, providing team instruction in safe work methods, and improved instruction in safe lifting techniques.

#### **For more information, contact:**

Terry L. Stentz: [tstentz1@unl.edu](mailto:tstentz1@unl.edu)

#### **Read the report**

<http://bit.ly/2WN3JGH>

©2019, CPWR-The Center for Construction Research and Training. All rights reserved. CPWR is the research and training arm of NABTU. Production of this document was supported by cooperative agreement OH 009762 from the National Institute for Occupational Safety and Health (NIOSH). The contents are solely the responsibility of the authors and do not necessarily represent the official views of NIOSH.



**THE CENTER FOR CONSTRUCTION  
RESEARCH AND TRAINING**

**[WWW.CPWR.COM](http://WWW.CPWR.COM)**